[Two Usages] AODELAN canon remote control can used for wireless or wired shutter release. Transmitter (with LCD screen) and receiver can be used for wireless function, C6 C8 connecting wire can be used for wired function that which can reduce camera shake and allows you to trigger your camera wirelessly up to 196 feet.Using 2.4G transmission technology more ultra- powerful anti-interference ability.
[4 modes for Shutter Release Control and 5 settings for Timing Control] S(single shooting), C (continuous shooting), B (bulb exposure), 2S (2 seconds delay); Timer (timer schedule shooting), DELAY (Delay Shooting Setting), long time exposure timer, Intvl (interval timer), N (number of exposures) and BKLN (auto bracketing timer to shoot multiple exposure HDR images).
[Saving Your Time But You Can Enjoy The Whole Process] Timing setting can be accurate to 0.1 seconds. Ideal for time-lapse photography to record the blooming flowers, sunsets or the night sky, but you dont need to wait for the whole time.
[Compatible cameras] Canon 90D, EOS RP, R, M5,M6,1D X Mark II,1D X,1D C,1Ds Mark III,1Ds Mark II,1Ds,1D Mark IV,1D Mark III,1D Mark II N,1D Mark II,1D,5D Mark IV,5D Mark III,5D Mark II,5DS R,5DS,5D,6D Mark II,6D,7D Mark II,7D,10D,20D,30D,40D,50D,60Da,60D,70D,77D (9000D),80D,D60,D30,EOS-1V,EOS-3, EOS Rebel T7 (2000D),T7i (800D),T6s (760D),T6i (750D),T6 (1300D),T5i (700D),T5 (1200D),T4i (650D),T3i (600D),T3 (1100D),T2i (550D),T1i (500D),XSi (450D),XTi (400D),XT (350D),XS (1000D),Contax N and 645
[Compatible cameras] Canon EOS M6 Mark II, Rebel (300D),SL2 (200D),SL1 (100D), Elan series, PowerShot SX70 HS,SX60 HS,SX50 HS,G1 X Mark III,G1 X Mark II,G1 X,G3 X,G5 X,G10,G11,G12,G15,G16; Fujifilm GFX 50R,X-T3,X-T2,X-T1,X-T100,X-E1,X-E2,X-E2s,X30,X100T,X-A5,X-Pro2,X-H1; Olympus OM-D E-M1 Mark II; Pentax K-1 Mark II,K10D,K20D,K100D,K110D,K200D,K-3,K-5,K-5 II,K-7,K30,K-50,K-500,*istDS,DS2,DS,DL2,DL,D; Samsung NX10,NX100,GX-1S,GX-1L,GX-10,GX-20;Hasselblad H series;Sigma SD1,SD9,SD10,SD14,SD15
canon eos remote control